

## **COAD<sup>®</sup>** **30** **Zinc** **Stearate** **Prill**

### **DESCRIPTION**

COAD<sup>®</sup> 30 Zinc Stearate Prill was developed especially for the polymer industry with a higher ash content and good heat stability. The prilled particle size and high bulk density enhances flow characteristics and reduces dust.

### **TYPICAL PROPERTIES**

Total Ash, %	15.3
Moisture, %	0.2
Free Fatty Acid, %	0.2
Soluble Salts, %	Nil
Softening Point, C	122
Apparent Density, lbs/ft <sup>3</sup>	42
% Thru 20 Mesh	99
% Thru 200 Mesh	5.0
Appearance	Free flowing white micro beads

### **APPLICATIONS**

- **Dry Blends:** COAD<sup>®</sup> 30 Zinc Stearate Prill reduces caking and improves flow properties while reducing dust. Due to its greater density, higher loadings can be obtained in certain equipment.

## ADDITIONAL INFORMATION

- Other – See SDS for COAD® 30 Zinc Stearate Prill for additional health, safety, and environmental information.
- Packaging – COAD® and MATHE Zinc Stearates are packaged in various sized multiwall bags and supersacks, unitized on non-returnable wooden pallets. Please contact your Norac sales representative to discuss your special packaging requirements.